



HANDLING EQUIPMENT

Spreader bars

BIL-T

We present you the BIL-T model of spreader bars.

Choose one of our **telescopic lifting spreader bars** as it adapts to any dimension and capacity need on the job site! The **male and female interlocking system** permits **multiple configurations**. You will be able to use each section individually or combined with other components. Easy to transport and store. Check the table below to find out the capacities and the min and max lengths.

This product is available also galvanized. Galvanized spreader bars maintain their characteristics over time; the hot-dip galvanization process forms a coating of corrosion-resistant zinc which prevents corrosive substances from reaching the more delicate part of the metal.

All our bars are built to meet or exceed the regulations of CE UNI-EN and ASME and come with the required labels, certificates and user and maintenance manual. All our products are covered by a 1-year warranty (EU Directive).



MODEL	MIN. LENGTH (mm)	MAX. LENGTH (mm)	MIN. CAPACITY (ton)	MAX. CAPACITY	OTHER DIMENSIONS
BIL-7/35T	2057	10543	7	35	SEE ATTACHED FILE
BIL-8/15T	1220	3049	8	15	SEE ATTACHED FILE
BIL-10/70T	2057	10723	10	70	SEE ATTACHED FILE
BIL-27/110T	2057	10543	27	110	SEE ATTACHED FILE



Boscaro srl

Via G. Cederle, 1 - 36020
Campiglia dei Berici (Vicenza) Italy

Tel +39 0444 866520
Fax +39 0444 866350
P.IVA: 00672450244